

15" LCD MONITOR

RackMore System



Fully closed.
Functions as a rack
mount monitor.



Monitor door
open.
Keyboard in
upright stowed
position.



Monitor door open.
Keyboard
lowered for use.
Allows access
to rear mounted
equipment.



Monitor door
closed with
keyboard lowered
ready for use.

RMST-715 shown with keyboard option.

Model Numbers:

RMST-715(X)



Keyed lock.

- Blank = No Lock
- L1 = Keyed lock
in place of
bottom latch.
- L2 = Keyed lock in
place of both
latches.

RackMore Systems are available with 10.4", 15" and 17" LCD monitors plus many additional attachments.

We offer OEM and custom solutions designed to fit your applications.

Contact us for additional information.



RACKMORE

The RackMore RMST-715 system contains a 15" LCD monitor mounted in a latched door. Monitor controls are mounted on the right edge of the door and are accessible when the door is open. With the door is open access is gained to equipment mounted to the RackMore frame.

A popular option is a keyboard which is accessed with the door open allowing the keyboard to be lowered for use. Once lowered, access is gained to the rear frame mounted equipment. The door is then closed and latched and is ready for use as a standard monitor and keyboard. If desired the door can be opened and the keyboard returned to the upright position, behind the monitor door and in front of the attached equipment, and the door can again be closed making the unit function as a monitor only. An optional lock is available in place of the standard door latch to obtain a fully secured unit when the door is closed and latched.

The 7U vertical rack space used in mounting the RackMore system is regained by attaching rack mounted equipment to the system frame via couplers in 7 1U increments. The couplers allow easy installation/removal of equipment with attachment access from the front of the system frame. This method allows equipment installation/removal without removing the total system from the rack. This attachment system allows the user to obtain the benefits of a rack mounted monitor and keyboard using virtually no rack space.

RMST-715 Product Specifications

Dimensions:

19.0" (W) x 12.22" (H) x 4.0" (D)

1U Attachment Spaces:

7

Weight:

21 lbs.

Display Input Power:

110-240 VAC, 50/60 Hz
via 12 VDC adapter

Temperature:

Operating > 0° to 50° C
Storage > -20° to -60° C

Humidity:

Operating > 10% to 90% RH Max

Colors Available:

Black standard
Others optional

Display Type:

15" active matrix TFT LCD

Colors Displayed:

16.7M

Contrast Ratio:

400:1 typ.

Brightness:

250 cd/m² typ.

Viewing Angle:

130°/100° H/V

Resolution:

VGA up to 1024x768

Response Time:

25ms typ.

Signal Inputs:

ARGB and DVI-D standard
Composite/S-Video optional



www.rackmore.com

sales@rackmore.com

1-800-729-7654

1620-A Berryessa Rd Tel: 408-928-1480
San Jose, CA 95133 Fax: 408-729-3661